

SAFETY DATA SHEET

conforms to 91/155/EC (ISO 11014)

1 IDENTIFICATION OF THE PRODUCT AND THE COMPANY

- 1.1. **Product:** Painting Medium quick drying 084
Art. no.: 2400.0084
- 1.2. **Company:** Royal Talens
Sophialaan 46, 7311 PD, Apeldoorn, the Netherlands
P.O. Box 4, 7300 AA, Apeldoorn, the Netherlands
Telephone +31 (0)55 - 5274700
Telefax +31 (0)55 - 5215286
www.talens.com

2 COMPOSITION AND INFORMATION ON INGREDIENTS

Dangerous components: White Spirit
% by weight: 55-65
CAS-no.: 64742-82-1
EINECS-no.: 265-185-4
Symbols: Xn, N
R-phases: 10, 51/53, 65, 66

3 HAZARDS IDENTIFICATION

Flammable. Dangerous for the environment.
For more information see 15.

4 FIRST-AID MEASURES

Inhalation: Move to fresh air.
Skin contact: Wash affected areas with soap and water.
Remove contaminated clothing
Eye contact: Flush immediately with large amounts of water. Consult a physician.
Ingestion: Drink one or two glasses of water to dilute. Do not induce vomiting. Consult a physician.

5 FIRE-FIGHTING MEASURES

Suitable: foam, CO₂, dry chemical.

6 ACCIDENTAL RELEASE MEASURES

Provide sufficient ventilation. Remove all sources of ignition. Absorb on a suitable substrate.

7 HANDLING AND STORAGE

Use only in well-ventilated areas. Store containers out of sun and away from heat, sparks and flames.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Provide sufficient ventilation to keep vapour-concentration low. Use protective gloves in case of prolonged or repeated contact. Wash hands before eating, drinking or smoking.

9 PHYSICAL AND CHEMICAL PROPERTIES

Characterization:	Cyclohexanon resin solution in mainly White Spirit and vegetable oils.	
Form:	Liquid	
Odour:	Solvent	
pH:		(20°C)
Viscosity:	8-10	mPa.s (20°C)
Boilingpoint/-range*:	> 157	°C
Meltingpoint/-range*:	n.a.	°C
Flashpoint*:	approx. 40	°C
Ignitiontemperature*:		°C
Explosionlimits*:	lower: 0.6 vol %; upper: 6.5 vol %	
Vapourpressure*:	3	mbar (20°C)
Density*:	0.87	g/cm ³ (20°C)
Solubility in water*:	insoluble	g/l
Solubility in white spirit*:	completely	g/l

* items tested in accordance with 67/548/EC

Other information:

10 STABILITY AND REACTIVITY

N.a.

11 TOXICOLOGICAL INFORMATION

Excessive inhalation of vapours may cause dizziness and headache. Prolonged skin contact may lead to extraction of natural oils with resultant mild irritation. Eye contact may cause irritation.

12 ECOLOGICAL INFORMATION

Avoid contamination of sewerage.

13 DISPOSAL CONSIDERATIONS

Comply with local regulations.

14 TRANSPORT INFORMATION

UN-no.: 1263
 Land ADR/RID: 3, 31c
 Water ADNR:
 Sea IMDG: 3.3
 Air ICAO/IATA-DGR: 3 III
 Other information:

15 REGULATORY INFORMATION

Labelling in accordance with directive 1999/45/EC.

Classification Flammable. Dangerous for the environment.



Symbol

Risk phrase R 10 - Flammable.
 R 51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R 66 - Repeated exposure may cause skin dryness or cracking.

Safety phrase S 2 - Keep out of reach of children.
 S 24 - Avoid contact with skin.
 S 29 - Do not empty into drains.
 S 46 - If swallowed, seek medical advice immediately and show this container or label.
 S 51 - Use only in well-ventilated areas.

16 OTHER INFORMATION