

# SAFETY DATA SHEET

## WINSOR & NEWTON GRIFFIN ALKYD FAST DRYING OIL COLOUR

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME WINSOR & NEWTON GRIFFIN ALKYD FAST DRYING OIL COLOUR  
PRODUCT NO. 1900000  
APPLICATION Fine Art Painting  
SUPPLIER Colart Fine Art & Graphics Limited  
Whitefriars Avenue  
Harrow  
Middlesex HA3 5RH  
+44 (0) 208 4274343  
44 (0) 208 42433217

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-butanone oxime	202-496-6	96-29-7	< 1%	Xn;R21. Carc 3;R40. Xi;R41. R43.
cobalt zirconium carboxylate in aliphatic hydrocarbon solution			< 1%	Xn;R65,R22. Xi;R38. R43.
distillates (petroleum), hydrotreated light	265-149-8	64742-47-8	10-30%	Xn;R65. R66.
Oil modified alkyd resin			10-30%	R66.

The Full Text for all R-Phrases are Displayed in Section 16

### 3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

#### HUMAN HEALTH

The product contains a sensitising substance which may provoke an allergic reaction among sensitive individuals.

### 4 FIRST-AID MEASURES

#### INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT INDUCE VOMITING! Immediately rinse mouth and provide fresh air. Get medical attention.

#### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### 6 ACCIDENTAL RELEASE MEASURES

#### SPILL CLEAN UP METHODS

Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Persons susceptible for allergic reactions should not handle this product.

#### STORAGE PRECAUTIONS

Store in closed original container in a dry place. Store in a cool and well-ventilated place. Keep separate from food, feedstuffs, fertilisers and other sensitive material.

# WINSOR & NEWTON GRIFFIN ALKYD FAST DRYING OIL COLOUR

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit

### HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

### EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste		
COLOUR	Misc. colours		
ODOUR	Hydrocarbon		
BOILING POINT (°C)	150-200 760 mm Hg	MELTING POINT (°C)	<0
RELATIVE DENSITY	1.2 -1.9 20.	VAPOUR PRESSURE	2. mm Hg 15 C
VOLATILE BY VOL. (%)	20.	FLASH POINT (°C)	70 CC (Closed cup).
AUTO IGNITION	>250	FLAMMABILITY LIMIT - LOWER(%)	0.9
TEMPERATURE (°C)			
FLAMMABILITY LIMIT - UPPER(%)	6.0		

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

### HAZARDOUS DECOMPOSITION PRODUCTS

High temperatures generate: Toxic gases/vapours/fumes of: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

May cause sensitisation by inhalation.

### INGESTION

May cause discomfort if swallowed.

### SKIN CONTACT

May cause sensitisation by skin contact.

### EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

## 12 ECOLOGICAL INFORMATION

# WINSOR & NEWTON GRIFFIN ALKYD FAST DRYING OIL COLOUR

## ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

## 13 DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION

ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not Classified.
SEA TRANSPORT NOTES	Not Classified.
AIR TRANSPORT NOTES	Not Classified.

## 15 REGULATORY INFORMATION

### RISK PHRASES

NC Not classified.

### SAFETY PHRASES

P14 Contains 2-butanone oxime, cobalt zirconium carboxylate in aliphatic hydrocarbon solution. May produce an allergic reaction.

### EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

## 16 OTHER INFORMATION

DATE 1/10/2007

### RISK PHRASES IN FULL

R21	Harmful in contact with skin.
R22	Harmful if swallowed.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.